

Emission Test Certificate

Wednesday November 25th, 2020

Supplier: Australian Select Timbers Pty Ltd (136 Atlas Boulevard, Dandenong South VIC, 3175, Australia)

Sample Description: Aurora European Oak

Date Tested: March 2014 (Tested through FORAY Laboratories - NATA Accreditation 1231)

Test Method: ASTM D5116-17 "Standard Guide for Small-Scale Environmental Chamber Determinations of Organic Emissions from Indoor Materials/Products".

Emission Data (24 hrs exposure):

Green Building Council of Australia Green Star Design & As Built V1.3 13.1.2B & 13.2 Green Star Interiors V1.3 - 12.1.2B	Aurora European Oak
Total Volatile Organic Compound Emission Rate limit:	Total Volatile Organic Compound
≤0.5 mg/m²/hr	Emission Rate: 0.008 mg/m ² /hr
4-phenylcyclohexene Emission Rate limit:	4-phenylcyclohexene Emission Rate:
<0.05mg/m²/hr	<0.005 mg/m²/hr
Formaldehyde Emission Rate limit: ≤ 0.1 mg/m ² /hr	Formaldehyde Emission: <0.007 ppm

Dr. Vyt Garnys PhD, BSc(Hons) AIMM, ARACI, ISIAQ ACA, AIRAH, FMA Managing Director and Principal Consultant

Ch.S.S. Comb

Srikanth C. Srivatsa PhD (Chemistry) Consultant

ATTANK

Tuan Duong PhD (Chemical Eng.) Senior Consultant

V2011075

OHS & Environmental Care