everline
vinyl plank

Australian Select Timbers®

Technical Data Sheet

2.5mm Everline Vinyl Plank

General Information

Size	1219mm x 178mm
Thickness	2.5mm
Surface Finish	Embossed Matte Finish
Pattern Variation	Moderate
Wear Layer	0.5mm
Core	PVC Composite
Back Layer	Dry Back
Profile	Square Edge
Pack Coverage	3.91m^2
Pack Weight	18.05kg
Pack Info	18 boards per pack – All full lengths
Pallet Packs	55
Application	Residential & Commercial
Maintenance	As per Australian Select Timbers - Everline Vinyl Plank's care & maintenance instructions - please refer to: asttimbers.com.au



Technical Data Sheet

2.5mm Everline Vinyl Plank

Installation

Floated directly on subfloor	No
Fully Bonded	Yes
Nailed	No
Floated on underlay	No
Over Heated Slab*	Yes*

*Please refer to our Installation Instructions and Heated Slab Installation Instructions for more information on our website. For commercial or multi-residential installations, if any additional underlay is required, a formal letter of authorisation from the manufacturer must be obtained prior to the installation.

Test Results & Certificates^

Acoustic Result*	L'nT,w: 52 (3 Star - AAAC Star Rating)
Wet Slip Test	AS 4586:2013 Classification: **P3**
Dry Slip Test	AS 4586:2013 Classification: **D1**
Oil Slip Test	AS 4586:2013 Classification: **R10**
Australian Reaction to fire – FLOOR	ASISO 9239.1-2003 Result CHF 9.5 kw/m^2 Smoke Value 142%.min
Release of formaldehyde	ASTM D5116 Result 0.004 mg/m^2/hr (max allowable 0.1)
Total VOC	ASTM D5116 Result 0.078mg/m^2/hr (max allowable 0.5)

^All test reports and certificates are available upon request. Acoustic test results are site specific (will vary from building to building), and as such, the above result is indicative only. Prior to purchase, Australian Select Timbers recommends carrying out an independent acoustic test for a site specific result.

*All testing conducted on 200mm concrete slab and a single layer of 10mm standard suspended plasterboard ceiling (with no insulation) as per B.C.A and AAAC requirements. Please contact Australian Select Timbers for further information regarding these test results.

Warranties

Warranty - Residential	Lifetime
Warranty - Commercial	10 Year

Lifetime Residential Warranty

10 Year Commercial Warranty

Installation & Warranty

All Everline Vinyl Plank floors must be installed by a competent approved installer who has all the necessary skills and take individual site circumstances into account. Everline Vinyl Plank warranty will only apply to floors which have been installed according to the installation instructions available in each pack and on the website – **asttimbers.com.au**

Terms & Conditions: Please note this technical sheet was written by Australian Select Timbers Pty Ltd. All the information is specified correctly while writing and publication of the sheet. The company reserves the right to change the specifications of this product at any time without prior notice to third parties.

Colour Disclaimer: We cannot guarantee that the colours you see printed on this technical data sheet or displayed on our website accurately portrays the true colours of the floorboards. Electrical device's monitors and/or screens are not calibrated equally and colour reproduction on the Internet is not precise. Swatch colours can be verified by ordering a complimentary offcut sample from our website or visiting an Australian Select Timbers' retail partner to view in-store.

Australian Select Timbers Pty Ltd.

asttimbers.com.au | 1300 901 355

23224-AUG26